

# Rubblizing in Illinois



David L. Lippert, P.E.

**Acting Engineer of Materials and Physical Research** 

**Illinois Department of Transportation** 




### Why Rubblization?

- Aging infrastructure
- Material durability of old PCC
- Multiple overlays on many routes
  - Reflective cracking problems
- What you put on the plans is what you get
  - No patching quantity creep
  - Known construction time
- Cost





# D-Cracking - a.k.a. "self-rubblization"





# Rubblizing

**PCC Slab** 

**AC** Overlay

Rubblized PCC Slab





## Rubblizing History

- First Project 1990 Part of SHRP-LTPP
  - I-70 near Pesotum
  - Used Resonant Breaker
  - Overlays of 6" and 8"
  - Concern Over Traffic Control
  - Felt Projects Should be Limited to Closed Roadways Due to Traffic Encroachment








## Equipment

- Multi-head breaker
  - Single pass
  - Z-Grid roller required
- Resonant frequency breaker
  - Multiple passes (18 to 20 per lane)



#### Project Selection Factors

- Existing pavement condition
- Subgrade
- Overhead clearances
- Transitions to mainline structures
- Utilities
- Proximity to buildings, other structures
- Underdrains



- 1990 First Project I-57 near Pesotum
  - PB-4
  - 6" and 8" Overlay of 10 Rubblized
- 1994 IL-38 Dist 2 and I-55 Front Rd.
  - PB-4
  - IL 38 6+1" over 9" Rubblized
  - I-55 FR 5" over 10" Rubblized
- 1996 I-57 Dist 7 near Edgewood
  - Multi-Head Breaker (MHB)
  - 6" and 8" Overlay of 8" Rubblized
- 1997 I-57 Dist 9 near Anna
  - MHB
  - 9" Overlay of 10" Rubblized
- 1997 I-70 Dist 5 near Greenup
  - MHB
  - 9, 10 and 11" Overlay of 8" Rubblized
- 1999 I-74 Dist 4 near Woodhull
  - MHB
  - 11" Overlay of 7" Rubblized
- 2003 I-70 Dist 5 near Marshall
  - 17.5" Overlay of 8" Rubblized




### Construction Sequence

- Install underdrains
- Mill existing overlays
- Widen if needed
- Replace unsound HMA patches
- Rubblize pavement
- Compact broken pavement
- Pave binder lifts (allow traffic if nec.)
- Pave surface lift


































#### Guideline Developed May 2000

- Requires soil investigation
- Selection of equipment
- 10Yr+ design
- Design thickness charts











#### Bituminous Overlay Thickness for Rubblized Pavements



—— Districts 1, 2 - - - Districts 7, 8, 9







#### Multi-Head Breaker





#### **Z-Grid Roller**





# Resonant Frequency Breaker





# **Project History**

- First project in 1990 near Pesotum
  - SHRP SPS-6 experiment
- 12 projects on State routes to date
  - 7 include experimental features
  - 1 designed with a 30-yr. design period



## Project Performance

- Automated data collection vehicles
  - IRI
  - Rutting
  - Digital imagery
- Manual distress surveys
- Falling weight deflectometer testing





































































## Conclusions

- Illinois' experience with rubblization has been a positive one.
- Rubblization is both reliable and costeffective.
- Properly constructed sections have performed as well, or better than, control sections.
- On average data indicates 1-2 years extra life with better performance.

# A. Lincoln Presidential Museum and Library





### Questions?

David L. Lippert

(217) 782-6732

Lippertdl@dot.il.gov

Charles J. Wienrank

(217) 782-6732

Wienrankcj@dot.il.gov

#### Web Report:

RUBBLIZING WITH BITUMINOUS CONCRETE OVERLAY

- 10 YEARS' EXPERIENCE IN ILLINOIS

Link:

http://www.dot.il.gov/materials/research/pdf/137.pdf